

BRIO-OX 44

ACQUACOREMEDY - USA

BRIO-OX 44 is classified as surface aerator. The best features of this equipment include circulation, degassing, oxygenation and at the same time low power consumption. These machines are compact and powerful. They feature a motor which can be tilted upward to produce a spray effect and provide for effective work in both oxygenating and degassing mode. BRIO-OX 44 can achieve good circulation within the basin thanks to a rear water booster which is designed to allow for destratification and to avoid working on the surface layer only, as is typically the case with traditional systems.



FEATURES

- Sturdy and durable
- Suitable for use in freshwater as well as in salt water
- Floating and dock mount support versions available
- Conveyor available to direct the flow in order to obtain a longer direct effect
- Lightweight, easy to handle and to move from tank to tank or from pond to pond

SUPPORTS



FLOATING INSTALLATION

Light-weight and easy to install, for standard aquaculture applications



DOCK MOUNTING INSTALLATION

Useful for lake de-icing, weeds/algae removal and destratification

SINGLE PHASE 230 V	THREE PHASE 400 V	NOM. POW. HP	NOM. POW. KW	AMP SINGLE PHASE	AMP THREE PHASE	CAPACITY L/M	R.P.M./1"	WEIGHT KG
BRIO-OX 44 0.5 M	BRIO-OX 44 0.5 T	0.5	0.37	2.7	1.6	1050	3350	15.5
BRIO-OX 44 1 M	BRIO-OX 44 1 T	1	0.75	5.3	2.1	2100	3350	16.5
BRIO-OX 44 1.5 M	BRIO-OX 44 1.5 T	1.5	1.1	7.7	3.0	3100	3350	16.5